

TYPE:

CAT. #:LBD400-C10-






LBD400-C10 ARTEMIS

The LBD400 series of LED Bollards are the latest addition to our growing line of innovative and exquisite area light luminaires. This series is available in seven elegant shade designs with three progressive sizes to complement our new LML pendants and LWM wall sconces. Our Thermally Integrated® and Field Serviceable LED modules provide superior heat dissipation, longer life, and higher performance. Ideal for illuminating grand pathways, estate-sized driveways, and expansive outdoor spaces.

Features include:

- 18 or 22 Watts
- 2700K (80 & 90 CRI) or 3000K (80 CRI)
- Thermally Integrated® w/ Copper Core Technology®
- 0-10V Dimming
- 100-277 VAC
- Solid Copper and Brass Construction






LBD400-C10-BLP



The Echo Collection™ from Auroralight are configurable and scale-able, Wall Sconce, Pendant and Bollard luminaires. This all-encompassing line of products was designed to complement one another while also providing the level customization everyone has come to expect from Auroralight.



Copper Core® is a registered trademark of Auroralight. It is synonymous with the mark of quality and integrity. It means that our products are built upon a superior foundation of Solid Copper, ensuring every critical part functions seamlessly together Thermally integrated® one component to the next. Auroralight manufactured without compromise, engineered with passion, in the USA.



SEE NEXT PAGE FOR ORDERING INFORMATION







TYPE: CAT. #:LBD400-C10-



LBD400-C10 ARTEMIS

ORDERING GUIDE: LBD400-C10 L (LED) BD (BOLLARD) 400 (SERIES) C (CONICAL) 10 (INCHES)

INDICATES REQUIRED FIELD (III) INDICATES OPTIONAL FIELD INCLUDED IN BASE PRICE [] QUICK SPEC (See Below)

QUICK SPEC SKU LBD400-C10-18-27-40-SM-NAT

LBD400-C10


WATTAGE

[18] 18 Watts
[27] 2700K, 80 CRI
[36] 36"

[22] 22 Watts

[279] 2700K, 90 CRI
[30] 3000K, 80 CRI
[40] 40"

NOTE: For other CCT and CRI options, contact factory












TYPE:	
CAT. #:LBD400-C10-	

LBD400-C10 ARTEMIS

PHOTOMETRIC OVERVIEW

Information based on 3000K. To download more in-depth IES photometric data, visit auroralight.com/product/lbd400-c10-artemis/

Mounting Height - 4 Feet



BUG Rating B0 U2 G1



