



UL Verification Services Inc.
7036 Snowdrift Road
Allentown, PA 18106
610-774-1300



Photometric Test Report

Relevant Standards
IES LM-79-2008, ANSI C82.77-2002

Prepared For
Auroralight Inc

2742 Loker Avenue West
Carlsbad
CA, 92010
United States

Catalog Number

HPL7-2-30

Order Number

11745044

Test Number

11745044.16

Test Date

2017-05-12

Prepared By

Javier Caban, Technician

Approved By

Tiffany Hamm, Project Handler

The results contained in this report pertain only to the tested sample.
This report shall not be reproduced, except in full, without written approval of Underwriters Laboratories.
This report must not be used by the client to claim product certification, approval, or endorsement by
NVLAP, NIST, or any agency of the Federal Government.



Luminaire Description: Conical 7" copper shade with clear glass lens, cylindrical copper stem and brass base
Lamp: 64 white LEDs
Mounting: Path/Area
Ballast/Driver: Integrated

Luminaire



Luminaire Characteristics

Luminous Diameter: 7.00 in.

Summary of Results

Roadway Classification: Type V, Very Short
Cutoff Classification: Semicutoff
BUG Rating: B0 U1 G0

Test Conditions

Test Temperature: 25.3 °C
Voltage: 12.00 VAC
Current: 0.2897 A
Power: 2.140 W
Power Factor: 0.615
Frequency: 60 Hz
Current THD: 89.8 %

Tested in 30 planes left side, 30 planes right side, left and right averaged
Vertical test increments are 2.5 degrees
Test distance exceeds five times the greatest luminous opening of luminaire

Laboratory results may not be representative of field performance
Ballast factors have not been applied



Distribution - Goniophotometer

Distribution Test Conditions

Temperature	Voltage	Current	Power	Power Factor	Frequency	Current THD
25.3 °C	12.00 VAC	0.2897 A	2.140 W	0.615	60 Hz	89.8 %

Summary of Results

Spacing Criteria

0-180: 1.02
90-270: 1.02

Total Lumen Output:

115.6 Lumens


Luminaire Efficacy:

54.0 lm/w

Maximum Candela:

34 Candela

Polar Plot



Zonal Lumen Summary

Zone	Lumens	% of Luminaire	Zone	Lumens	% of Luminaire	Zone	Lumens	% of Luminaire
0-5	0.76	0.7%	60-65	10.79	9.3%	120-125	0.01	0.0%
5-10	2.35	2.0%	65-70	10.83	9.4%	125-130	0.01	0.0%
10-15	3.30	2.9%	70-75	10.40	9.0%	130-135	0.01	0.0%
15-20	4.19	3.6%	75-80	8.81	7.6%	135-140	0.01	0.0%
20-25	4.94	4.3%	80-85	4.56	3.9%	140-145	0.01	0.0%
25-30	5.50	4.8%	85-90	0.91	0.8%	145-150	0.01	0.0%
30-35	5.89	5.1%	90-95	0.20	0.2%	150-155	0.01	0.0%
35-40	6.46	5.6%	95-100	0.08	0.1%	155-160	0.01	0.0%
40-45	7.33	6.3%	100-105	0.04	0.0%	160-165	0.01	0.0%
45-50	8.40	7.3%	105-110	0.03	0.0%	165-170	0.01	0.0%
50-55	9.43	8.2%	110-115	0.02	0.0%	170-175	0.00	0.0%
55-60	10.22	8.8%	115-120	0.02	0.0%	175-180	0.00	0.0%

Zone	Lumens	% of Luminaire
0-40	33	28.9%
0-60	69	59.5%
0-90	115	99.5%
90-180	0	0.4%



Candela Tabulation

Horizontal Angle (Degrees)

Vertical Angle (Degrees)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5
	0	31.05	31.05	31.05	31.05	31.05	31.05	31.05	31.05	31.05	31.05	31.05	31.05	31.05	31.05	31.05
	5	32.36	32.36	32.36	32.36	32.36	32.36	32.36	32.36	32.36	32.36	32.36	32.36	32.36	32.36	32.36
	10	30.03	30.03	30.03	30.03	30.03	30.03	30.03	30.03	30.03	30.03	30.03	30.03	30.03	30.03	30.03
	15	26.42	26.42	26.42	26.42	26.42	26.42	26.42	26.42	26.42	26.42	26.42	26.42	26.42	26.42	26.42
	20	24.60	24.60	24.60	24.60	24.60	24.60	24.60	24.60	24.60	24.60	24.60	24.60	24.60	24.60	24.60
	25	22.60	22.60	22.60	22.60	22.60	22.60	22.60	22.60	22.60	22.60	22.60	22.60	22.60	22.60	22.60
	30	20.81	20.81	20.81	20.81	20.81	20.81	20.81	20.81	20.81	20.81	20.81	20.81	20.81	20.81	20.81
	35	19.53	19.53	19.53	19.53	19.53	19.53	19.53	19.53	19.53	19.53	19.53	19.53	19.53	19.53	19.53
	40	19.45	19.45	19.45	19.45	19.45	19.45	19.45	19.45	19.45	19.45	19.45	19.45	19.45	19.45	19.45
	45	20.24	20.24	20.24	20.24	20.24	20.24	20.24	20.24	20.24	20.24	20.24	20.24	20.24	20.24	20.24
	50	21.30	21.30	21.30	21.30	21.30	21.30	21.30	21.30	21.30	21.30	21.30	21.30	21.30	21.30	21.30
	55	22.00	22.00	22.00	22.00	22.00	22.00	22.00	22.00	22.00	22.00	22.00	22.00	22.00	22.00	22.00
	60	22.23	22.23	22.23	22.23	22.23	22.23	22.23	22.23	22.23	22.23	22.23	22.23	22.23	22.23	22.23
	65	21.94	21.94	21.94	21.94	21.94	21.94	21.94	21.94	21.94	21.94	21.94	21.94	21.94	21.94	21.94
	70	20.72	20.72	20.72	20.72	20.72	20.72	20.72	20.72	20.72	20.72	20.72	20.72	20.72	20.72	20.72
	75	18.99	18.99	18.99	18.99	18.99	18.99	18.99	18.99	18.99	18.99	18.99	18.99	18.99	18.99	18.99
	80	12.63	12.63	12.63	12.63	12.63	12.63	12.63	12.63	12.63	12.63	12.63	12.63	12.63	12.63	12.63
	85	4.35	4.35	4.35	4.35	4.35	4.35	4.35	4.35	4.35	4.35	4.35	4.35	4.35	4.35	4.35
	90	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44	0.44
	95	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
	100	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
	105	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.06
	110	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05
	115	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04
	120	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03
	125	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03
	130	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03
	135	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03
	140	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03
	145	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03	0.03
	150	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04
	155	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04
	160	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04
	165	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05
	170	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04
	175	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04
	180	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04

Average Luminance (cd/m²)

Horizontal Angle (Degrees)


Vertical Angle (Degrees)	Horizontal Angle (Degrees)			
	0	45	90	
	0	1251	1251	1251
	45	1153	1153	1153
	55	1545	1545	1545
	65	2091	2091	2091
	75	2955	2955	2955
	85	2008	2008	2008



Utilization of Lumens - Zonal Cavity Method

Effective Floor Cavity Reflectance 20%																		
Ceiling Cavity Reflectance	80				70				50			30			10			0
Wall Reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Room Cavity Ratio (RCR)	** Values are expressed as Lumens delivered to the task surface **																	
0	137	137	137	137	134	134	134	134	128	128	128	123	123	123	117	117	117	115
1	121	114	108	102	118	111	105	100	106	101	97	101	97	93	97	94	90	88
2	108	96	86	77	104	93	84	76	89	81	74	85	78	72	81	75	71	68
3	96	81	70	61	93	79	69	60	76	67	59	72	64	58	69	62	57	54
4	87	71	59	50	84	69	58	49	66	56	48	63	54	47	60	53	47	44
5	79	62	50	41	77	61	50	41	58	48	41	56	47	40	53	46	39	37
6	73	56	44	35	71	54	43	35	52	42	35	50	41	34	48	40	34	31
7	67	50	39	31	65	49	38	31	47	37	30	45	36	30	43	36	30	27
8	63	45	35	27	61	45	34	27	43	33	27	41	33	27	40	32	26	24
9	58	42	31	24	57	41	31	24	39	30	24	38	30	24	37	29	24	21
10	55	38	28	22	53	38	28	22	36	28	22	35	27	22	34	27	21	19


Beam and Field Information	
CIE Type:	Direct
Center Beam Intensity:	31.05 Candela
Central Cone Intensity:	31 Candela
Beam Flux:	106.9 Lumens
Beam Angle (0-180):	156.6 Degrees
Beam Angle (90-270):	156.6 Degrees
Field Angle (0-180):	171.7 Degrees
Field Angle (90-270):	171.7 Degrees

Cone of Light Tabulation			
Mounting Height (Feet)		Footcandles at Nadir	Diameter (Feet)
4.00		1.94	4.07
6.00		0.863	6.11
8.00		0.485	8.15
10.0		0.311	10.2
12.0		0.216	12.2
14.0		0.158	14.3
16.0		0.121	16.3



ISOFootcandle Plot

Mounting Height - 2 Feet



Grid Lines in Units of Mounting Height





IES "BUG" Rating
(Back Light, Uplight, Glare)
Per IES TM-15-11



Luminaire Classification System (LCS)

LCS	Zone	Lumens	Luminaire %
FL	(0-30)	10.5	9.1%
FM	(30-60)	23.8	20.7%
FH	(60-80)	20.3	17.6%
FVH	(80-90)	2.8	2.4%
BL	(0-30)	10.5	9.1%
BM	(30-60)	23.8	20.7%
BH	(60-80)	20.3	17.6%
BVH	(80-90)	2.8	2.4%
UL	(90-100)	0.3	0.2%
UH	(100-180)	0.2	0.2%
Total		115.3	100.0%
BUG Rating	B0 U1 G0		